



Axial / Radial / MELF

型番	パッケージタイプ	I/O	ピッチ
			(mm)
02445 021 6215	Stud Mount	2	0.000
02446 022 6215		2	0.000
02991 201 6215A		20	5.080
02991 251 6215A		25	5.080
02991 251 X2X5		25	5.080
02992 101 6215A		10	5.080
02992 101 6218F		6	5.080
02992 102 6215		10	5.080
02992 181 6215A		18	5.080
02992 201 6215A		20	5.080
02992 251 6215A		25	5.080
02992 251 6218A		9	15.240
02992 251 6218B		8	15.240
02992 251 6218D		25	5.080
02992 252 6215		25	5.080
03186 021 6215		2	0.000
03186 021 X2X8		2	0.000
03312 251 6251		25	4.572
03335 121 6215	Res / Cap	2	0.000
03337 161S6218Y	Kemet Tantalum	2	0.000
03343 081 6215		3	0.000
03344 061 6215		3	0.000
03451 041 6218B		2	0.000
03451 041 6218C		2	0.000
03451 041 6218D		2	0.000
03451 041 X2X5B		2	0.000
03480 101 6215		2	0.000
03481 101 6215		2	0.000
03481 101 6218		2	0.000
03532 021 6215	Dual Diode	2	3.302
03533 021 6215	Hybrid	2	4.826
03533 031 6215		3	3.810
03533 061 6215		6	3.175
03533 061 6218D		6	3.175
03533 061 6218E		6	3.175
03533 081 6215		8	4.826

型番	パッケージタイプ	I/O	ピッチ
			(mm)
03533 081 6218A		4	4.826
03533 091 6215		9	2.540
03533S081 6215		8	3.759
03546 191 6215		19	5.080
03546 191 6218		19	5.080
03547 211 6215		21	5.080
03547 211 6218		21	5.080
03549 201 6215		20	5.715
03555 021 6215		2	7.620
035XX SKT SET		22	2.540
03600 061 6218A		6	5.080
03600 081 6218A		8	5.080
03600 082 6215		16	5.080
03600 241 ASSY		24	0.000
03600 251 6215		25	5.080
03600 251 6218B		14	5.080
03600 251 6218C		10	5.080
03600 251 6218E		8	5.080
03600 252 6215		25	5.080
03630 251 6215		25	7.620
03630 251 6218K		15	7.620

Design Features

- Building Block Stripsockets for Automated Carrier Packaging
- Accepts Multiple-lead Diameters
- Excellent Contact Design for Wiping Action on Lead's Diameter
- Tailored for Production and Burn-in Testing
- Modifications Available
- Kelvin and Double-sided Contacts