



DIP

(Dual In-line Package)

型番	パッケージタイプ	パッケージ名	I/O	ピッチ	列間ピッチ
				(mm)	(mm)
02758 141 6215	Side-brazed DIP	Side-brazed DIP	14	355.60	7.62
02758 161 6215	Side-brazed DIP	Side-brazed DIP	16	406.40	7.62
02758 181 6215	Side-brazed DIP	Side-brazed DIP	18	457.20	10.16
02758 201 6215	Side-brazed DIP	Side-brazed DIP	20	508.00	7.62
02758 201 6218B	Side-brazed DIP	Side-brazed DIP	16	406.40	0.00
02758 221 6211	Side-brazed DIP	Side-brazed DIP	22	558.80	10.16
02758 241 6211	Side-brazed DIP	Side-brazed DIP	24	609.60	15.24
02758 281 X2X1	Side-brazed DIP	Side-brazed DIP	28	711.20	15.24
02758 282 6215	Side-brazed DIP	Side-brazed DIP	28	711.20	15.24
02758 401 6211	Side-brazed DIP	Side-brazed DIP	40	1016.00	15.24
02758 401 6218A	Side-brazed DIP	Side-brazed DIP	32	812.80	15.24
02758 641 6218	DIP	DIP	64	1625.60	25.40
02970/02997 Assy	DIP	DIP	26	660.40	0.00
02993 121 6215	DIP	DIP	12	304.80	22.86
03000 182 0428	Side-brazed DIP	Side-brazed DIP	18	457.20	15.24
03000 482 642C	Side-brazed DIP	Side-brazed DIP	48	1219.20	15.24
03111 141 6215	DIP	DIP	14	355.60	7.62
03111 161 6215	DIP	DIP	16	406.40	7.62
03111 181 6215	DIP	DIP	18	457.20	7.62
03111 201 6215	DIP	DIP	20	508.00	7.62
03111 201 6218	DIP	DIP	40	1016.00	7.62
03111 201 6218A	DIP	DIP	16	406.40	7.62
03111 221 6215	DIP	DIP	22	558.80	10.16
03111 241 6215	DIP	DIP	24	609.60	15.24
03111 281 6215	DIP	DIP	28	711.20	15.24
03111 401 6215	DIP	DIP	40	1016.00	15.24
03112 281 6215	DIP	DIP	28	711.20	7.62
03112 281 6218A	DIP	DIP	28	711.20	7.62
03140 192 6215	Hybrid DIP	Hybrid DIP	19	482.60	22.35
03140 432 6215	Hybrid DIP	Hybrid DIP	43	1092.20	38.86
03235 241 6215	DIP	DIP	24	609.60	7.62
03235 241 6218	DIP	DIP	20	508.00	0.00
03235 241 6218A	DIP	DIP	16	406.40	7.62
03235 241 6218B	DIP	DIP	12	304.80	7.62
03235 241 6218D	DIP	DIP	10	254.00	0.00
03235 241 6218E	DIP	DIP	6	152.40	0.00

型番	パッケージタイプ	パッケージ名	I/O	ピッチ	列スペース
				(mm)	(mm)
03235 301 6218D	DIP	DIP	30	762.00	10.16
03235 401 6215	DIP	DIP	40	1016.00	10.16
03545 202 6218H	DIP	DIP-8	8	203.20	0.00
03570 271 6217	DIP	SPM27-BA & BB	27	685.80	0.00

Design Features

High-side Contacts Accept Misaligned Leads

Positive Contact Wiping Action

Easy Removal with Dipstick Unloading Tool or Fingertip Insertion and Withdrawal

Standoffs Help Board Cleaning and Decrease Solder Wicking

Forgiving Long-life Contacts